

CDECIEICATIONS

	HP50X
Frequency Range	400-470MHz 136-174MHz
Channel Capacity	256
Zone Capacity	16
Zone Channels	16
Channel Spacing	12.5kHz/20kHz/25kHz
Operating Voltage	7.4V (rated)
Battery	2,400 mAh Li-ion
Battery Life (5/5/90)	Digital: 23h (GPS off) Digital: 21h (GPS on)
Frequency Stability	±0.5ppm
Antenna Impedance	50Ω
Dimensions (H x W x D)	119 mm x 55 mm x 33.5 mm
Weight (with antenna & battery)	300g (±5g)
BT	BT 5.3
Receiver	
Sensitivity	Analog: 0.18μV (12dB SINAD); 0.16μV (Typical) (12dB SINAD) Digital: 0.18μV/BER5%
Adjacent Channel Selectivity	TIA-603: 60dB@12.5kHz; 70dB@20/25kHz ETSI: 60dB@12.5kHz; 70dB@20/25kHz
Intermodulation	TIA-603: 70dB@12.5/20/25kHz ETSI: 65dB@12.5/20/25kHz
Spurious Response Rejection	TIA-603: 70dB@12.5/20/25kHz ETSI: 70dB@12.5/20/25kHz
Blocking	TIA-603: 80dB ETSI: 84dB
Hum and Noise	40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz
Rated Audio Power Output	0.5W
Rated Audio Distortion	≤3%
Audio Response	+1 ~ -3dB
Conducted Spurious Emission	<-57dBm
Transmitter	
RF Power Output	UHF: 1W/4W VHF: 1W/5W
FM Modulation	11K0F3E@12.5kHz 14K0F3E@20kHz
	16K0F3E@25kHz
	_
4FSK Digital Modulation	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD
4FSK Digital Modulation Conducted/Radiated Emission	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm<1GHz; -30dBm>1GHz
4FSK Digital Modulation Conducted/Radiated Emission Modulation Limiting	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm<1GHz; -30dBm>1GHz
4FSK Digital Modulation Conducted/Radiated Emission Modulation Limiting FM Hum & Noise	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm<1GHz; -30dBm>1GHz ±2.5kHz@12.5kHz;±4.0kHz@20kHz; ±5.0kHz@2
4FSK Digital Modulation Conducted/Radiated Emission Modulation Limiting FM Hum & Noise Adjacent Channel Power	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm<1GHz; -30dBm>1GHz ±2.5kHz@12.5kHz; ±4.0kHz@20kHz; ±5.0kHz@2 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz
4FSK Digital Modulation Conducted/Radiated Emission Modulation Limiting FM Hum & Noise Adjacent Channel Power Audio Response Audio Distortion	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm<1GHz; -30dBm>1GHz ±2.5kHz@12.5kHz; ±4.0kHz@20kHz; ±5.0kHz@2 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz 60dB@12.5kHz; 70dB@20/25kHz +1 to -3dB ≤3%
4FSK Digital Modulation Conducted/Radiated Emission Modulation Limiting FM Hum & Noise Adjacent Channel Power Audio Response Audio Distortion Digital Vocoder Type	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm<1GHz; -30dBm>1GHz ±2.5kHz@12.5kHz; ±4.0kHz@20kHz; ±5.0kHz@2 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz 60dB@12.5kHz; 70dB@20/25kHz +1 to -3dB
4FSK Digital Modulation Conducted/Radiated Emission Modulation Limiting FM Hum & Noise Adjacent Channel Power Audio Response Audio Distortion Digital Vocoder Type Environmental	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm<1GHz; -30dBm>1GHz ±2.5kHz@12.5kHz;±4.0kHz@20kHz;±5.0kHz@2 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz 60dB@12.5kHz; 70dB@20/25kHz +1 to -3dB ≤3% AMBE+2™/SELP
4FSK Digital Modulation Conducted/Radiated Emission Modulation Limiting FM Hum & Noise Adjacent Channel Power Audio Response Audio Distortion Digital Vocoder Type Environmental Operating Temperature	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm<1GHz; -30dBm>1GHz ±2.5kHz@12.5kHz;±4.0kHz@20kHz;±5.0kHz@2 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz 60dB@12.5kHz; 70dB@20/25kHz +1 to -3dB ≤3% AMBE+2™/SELP
4FSK Digital Modulation Conducted/Radiated Emission Modulation Limiting FM Hum & Noise Adjacent Channel Power Audio Response Audio Distortion Digital Vocoder Type Environmental Operating Temperature	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm<1GHz; -30dBm>1GHz ±2.5kHz@12.5kHz;±4.0kHz@20kHz;±5.0kHz@2 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz 60dB@12.5kHz; 70dB@20/25kHz +1 to -3dB ≤3% AMBE+2™/SELP
4FSK Digital Modulation Conducted/Radiated Emission Modulation Limiting FM Hum & Noise Adjacent Channel Power Audio Response Audio Distortion Digital Vocoder Type Environmental Operating Temperature Storage Temperature	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm<1GHz; -30dBm>1GHz ±2.5kHz@12.5kHz;±4.0kHz@20kHz;±5.0kHz@2 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz 60dB@12.5kHz; 70dB@20/25kHz +1 to -3dB ≤3% AMBE+2™/SELP
4FSK Digital Modulation Conducted/Radiated Emission Modulation Limiting FM Hum & Noise Adjacent Channel Power Audio Response Audio Distortion Digital Vocoder Type Environmental Operating Temperature Storage Temperature	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm < 1GHz; -30dBm > 1GHz ± 2.5kHz@12.5kHz; ± 4.0kHz@20kHz; ± 5.0kHz@2 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz 60dB@12.5kHz; 70dB@20/25kHz +1 to -3dB ≤3% AMBE+2™/SELP -20°C* ~ +60°C -40°C~ +85°C IEC 61000-4-2 (Level 4) ±8kV (contact);
4FSK Digital Modulation Conducted/Radiated Emission Modulation Limiting FM Hum & Noise Adjacent Channel Power Audio Response Audio Distortion Digital Vocoder Type Environmental Operating Temperature Storage Temperature ESD Dustproof & Waterproof	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm<1GHz; -30dBm>1GHz ±2.5kHz@12.5kHz; ±4.0kHz@20kHz; ±5.0kHz@2 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz 60dB@12.5kHz; 70dB@20/25kHz +1 to -3dB ≤3% AMBE+2™/SELP -20°C* ~ +60°C -40°C~ +85°C IEC 61000-4-2 (Level 4) ±8kV (contact); ±15kV (air)
4FSK Digital Modulation Conducted/Radiated Emission Modulation Limiting FM Hum & Noise Adjacent Channel Power Audio Response Audio Distortion Digital Vocoder Type Environmental Operating Temperature Storage Temperature ESD Dustproof & Waterproof Humidity	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm<1GHz; -30dBm>1GHz ±2.5kHz@12.5kHz; ±4.0kHz@20kHz; ±5.0kHz@2 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz 60dB@12.5kHz; 70dB@20/25kHz +1 to -3dB ≤3% AMBE+2™/SELP -20°C* ~ +60°C -40°C~ +85°C IEC 61000-4-2 (Level 4) ±8kV (contact); ±15kV (air) IEC60529-IP67
4FSK Digital Modulation Conducted/Radiated Emission Modulation Limiting FM Hum & Noise Adjacent Channel Power Audio Response Audio Distortion Digital Vocoder Type Environmental Operating Temperature Storage Temperature ESD Dustproof & Waterproof Humidity Shock and Vibration	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm < 1GHz; -30dBm > 1GHz ±2.5kHz@12.5kHz; ±4.0kHz@20kHz; ±5.0kHz@2 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz 60dB@12.5kHz; 70dB@20/25kHz +1 to -3dB ≤3% AMBE+2™/SELP -20°C* ~ +60°C -40°C~ +85°C IEC 61000-4-2 (Level 4) ±8kV (contact); ±15kV (air) IEC60529-IP67 MIL-STD-810H
4FSK Digital Modulation Conducted/Radiated Emission Modulation Limiting FM Hum & Noise Adjacent Channel Power Audio Response Audio Distortion Digital Vocoder Type Environmental Operating Temperature Storage Temperature ESD Dustproof & Waterproof Humidity Shock and Vibration Location Services	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm < 1GHz; -30dBm > 1GHz ±2.5kHz@12.5kHz; ±4.0kHz@20kHz; ±5.0kHz@2 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz 60dB@12.5kHz; 70dB@20/25kHz +1 to -3dB ≤3% AMBE+2™/SELP -20°C* ~ +60°C -40°C~ +85°C IEC 61000-4-2 (Level 4) ±8kV (contact); ±15kV (air) IEC60529-IP67 MIL-STD-810H
4FSK Digital Modulation Conducted/Radiated Emission Modulation Limiting FM Hum & Noise Adjacent Channel Power Audio Response Audio Distortion Digital Vocoder Type Environmental Operating Temperature Storage Temperature ESD Dustproof & Waterproof Humidity Shock and Vibration Location Services GNSS	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm<1GHz; -30dBm>1GHz ±2.5kHz@12.5kHz; ±4.0kHz@20kHz; ±5.0kHz@2 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz 60dB@12.5kHz; 70dB@20/25kHz +1 to -3dB ≤3% AMBE+2™/SELP -20°C* ~ +60°C -40°C~ +85°C IEC 61000-4-2 (Level 4) ±8kV (contact); ±15kV (air) IEC60529-IP67 MIL-STD-810H MIL-STD-810H
4FSK Digital Modulation Conducted/Radiated Emission Modulation Limiting FM Hum & Noise Adjacent Channel Power Audio Response Audio Distortion Digital Vocoder Type Environmental Operating Temperature Storage Temperature ESD Dustproof & Waterproof Humidity Shock and Vibration Location Services GNSS TTFF(Time To First Fix) Hot Start	16K0F3E@25kHz 12.5kHz Data Only: 7K60FXD 12.5kHz Data and Voice: 7K60FXW -36dBm<1GHz; -30dBm>1GHz ± 2.5kHz@12.5kHz; ± 4.0kHz@20kHz; ± 5.0kHz@2: 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz 60dB@12.5kHz; 70dB@20/25kHz +1 to -3dB ≤3% AMBE+2™/SELP -20°C* ~ +60°C -40°C~ +85°C IEC 61000-4-2 (Level 4) ±8kV (contact); ±15kV (air) IEC60529-IP67 MIL-STD-810H MIL-STD-810H

Hytera Communications Corporation Limited

Address: Hytera Tower, Hi-Tech Industrial Park North, 9108# Beihuan Road,

Tel: +86-755-2697 2999 Fax: +86-755-8613 7139 Post: 518057

Http://www.hytera.com marketing@hytera.com

Stock Code: 002583.SZ

Nanshan District, Shenzhen, P.R.C.

Hytera

ACCESSORIES • Standard







Optional









Antenna



Belt clip



 Waterproof Remote Speaker Microphone(IP67)



Noise-cancelling Headset



 Programming cable (USB port)



Earpiece with Transparent Acoustic Tube(Black)



Multi-unit charger







Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated

HYT, Hytera are registered trademarks of Hytera Communications Corp., Ltd. ©2024 Hytera Communications Corp., Ltd. All Rights Reserved.



When your people are working in potentially explosive environments such as chemical factory, oil refinery, firefighting and mining field, their safety is always your paramount concern. Hytera HP50X intrinsically safe digital portable radio is the right solution for your needs.

From inside to outside, the HP50X can confront any harsh conditions and offer reliable one-to-one or one-to-many communications, without compromising ease of use. Meanwhile, it delivers louder and clearer audio, extended coverage, and longer battery life. So the HP50X empowers your people to work safely and efficiently even in the most demanding environments.

- Explosion-proof Battery Identification
- Al-based Noise Cancellation
- USB Type-C port
- Analog-digital Compatibility
- Extended Communication Distance
- Longer-lasting Battery
- Light and Compact
- IP67
- Programmable Keys

Safety that thinks ahead.



UL913 Intrinsically safe

Peace of mind in hazardous area

Certified by the SGS agency and in strict compliance with the UL913 and TIA4950 standards, the radio is specifically designed for use in dangerous conditions with potentially combustible dust, flammable liquids, and explosive gas. No matter how extreme the working environment is, the radio can always provide reliable and efficient communications.



Multiple safety mechanisms Prepare for the unexpected

The radio has a suite of proactive approaches to safety. It can intelligently detect whether the battery is anti-counterfeiting and explosion-proof, preventing the risk or fire and explosion posed by the use of non-anticounterfeiting and non-explosion-proof battery. Also this radio provides Lone Worker and Emergency Alarm to make your people call for help quickly in case of an emergency, and the radio can send its location to the command center at the same time so that your people can be easily and accurately pinpointed thanks to the GPS and GLONASS positioning systems.



Superior audio quality

Make voice hear and heard, clearly

From high-power speaker to Al-based noise cancellation, as innovated and tested by Hytera Audio Lab*, the radio makes your people hear and be heard clearly even in noisiest environments. The Al-based noise cancellation technology helps the radio filter out the ambient noise including breathes, extract the human voice, and eliminate the annoying howling occurred by radios that are 30 cm away from each other.

* Hytera Professional Lab.

High RX sensitivity Stay connected, stay safe.

With enhanced RF solution from Hytera RF&Antenna Lab* adopted, the receiving sensitivity of every frequency band is improved up to $0.18 \,\mu\text{V}$ ($-122 \,\text{dBm}$). No matter whether the radio is in the area with weaker signal strength or at long range, it can always provide reliable communications for individuals or groups across your team to enhance safety and efficiency.

* Hytera Professional Lab.





Longer-lasting battery Meet multiple shifts on one charge

The radio comes with a standard 2,400 mAh Li-ion battery and boasts the best-in-class power saver technology innovated by Hytera Energy-efficient Lab*, so the radio can work up to 23 hours in digital mode and high power mode on a 5-5-90 duty cycle. Longer-lasting battery means that the radio can work for your people all the time to keep them connected, and further keeping connected is keeping safe.

* Hytera Professional Lab.



















